Modular & scalable UPS systems















DELPHYS Xtend GP

Real hot-scalable UPS system

Green Power 2.0 range up to 2.4 MVA/MW



DELPHYS XTEND GP combines all the benefits of the Green Power 2.0 technology and the flexibility of a modular system and provides easy adaptation to evolving requirements, without impacting the surrounding electrical infrastructure.

DELPHYS XTEND GP is a real scalable UPS system designed to provide power scalability that can be built up with power blocks to extend the system according to the maximum power requirement.

DELPHYS XTEND GP power scalability is provided by Xmodule power blocks docked onto prewired Xbay docks. The installation and the positioning are easy with secured operation both for operators and the application. During system extensions or maintenance, the load is fully protected in online double conversion mode.

Real hot-scalable solution

- Reliable power that can be increased when needed.
- Load fully protected in VFI mode during system extensions and maintenance.
- Prewired system providing quick and safe power scalability.

Total system adaptability

- Many disposition possibilities.
- Distributed or centralised static bypass.
- Shared or distributed batteries.
- AC and DC power connections flexibility.

Optimized capital employed

- Lower initial and operating costs.
- No modification to the site's electrical infrastructure during power upgrading.
- Optimized maintenance expenditure.
- BCR (Battery Capacity Re-injection), innovative battery discharge test.

Full set of services

- Preventive maintenance.
- 24 / 7 Hot-Line and remote monitoring.
- Quick response time to site and availability of new modules.
- Cabling & docking.
- OPEX-based costing models.

The solution for

- > Large data centers
- > Telecommunications
- > Healthcare sector
- > Service sector
- > Infrastructure
- > Processes
- > Industrial applications

Attestations and certifications



Advantages















Xmodule - designed to save costs

Energy performance

Based on DELPHYS GP 200 kW, the system has all the advantages of the Green Power 2.0:

- > Minimised energy consumption and cooling costs in VFI mode,
- Unitary power factor provides the best €/kW ratio,
- > Performance attested by Bureau Veritas.



Flexible UPS architecture

- Scalable power and energy storage capability.
- Distributed or centralised static bypass.
- Common or separated rectifier and bypass mains.
- Can be connected to shared or distributed batteries for energy storage optimisation.
- Compatible with different energy storage technologies.
- Systems parallelisation up to 2,4 MW

Standard electrical features

- Integrated maintenance bypass
- Backfeed protection: detection circuit.
- EBS (expert Battery System) for battery management.
- Battery temperature sensor.

Electrical options

- Extended battery charger capability.
- Flywheel compatible.
- ACS synchronisation system.
- BCR (Battery Capacity Re-injection).
- FAST ECOMODE.

Standard communication features

- User-friendly multilingual interface with graphic display.
- 2 slots for communication options.
- Ethernet connection (WeB/SNmP/email).
- USB port for event log access.


Communication options

- Advanced server shutdown options for stand-alone and virtual servers.
- ADC interface (configurable voltage-free contacts).
- MODBUS TCP.
- MODBUS RTU.
- BACnet/IP interface.

Remote monitoring service

 LINK-UPS, remote monitoring service that connects your UPS to your Critical Power specialist 24/7.

Dimensions



Integration ⁽¹⁾	Number of Xbay dock	W (mm)
Distributed bypass	4	4340
(common or separated input)	5	5050
	6	5760

(1) For any other configuration (centralized bypass, "U" shape, "L" shape, etc.), please contact us.

Technical data

		DELPHYS Xtend GP											
SYSTEM CONF	IGURATION												
Xmodule rated power		200 kVA/kW											
Number of Xbay docks		4			5				6				
Number of Xmodule power blocks (200 kVA/kW)		2	3	4	2	3	4	5	2	3	4	5	6
	N configuration	400	600	800	400	600	800	1000	400	600	800	1000	1200
Power (kVA/kW)	N+1 redundant configuration	200	400	600	200	400	600	800	200	400	600	800	1000
Max. power (syster	Max. power (systems in parallel)			up to 2400 kVA/kW (12 Xmodule)									
RECTIFIER INP	RECTIFIER INPUT ⁽¹⁾												
Voltage					400 V	3ph (2	00 to 48	30 V ⁽²⁾)					
Frequency						50/6	0 Hz						
Power factor						> 0	.99						
Total harmonic dist	tortion (THDI) at full age	2.5%®											
INVERTER													
Power factor		1 (according to IEC/EN 62040-3)											
Rated output voltag	400 V 3ph + N (380 / 415 V configurable)												
Rated output frequ	50/60 Hz (selectable)												
Harmonic voltage of	ThdU ≤ 1.5 % with rated linear load												
BYPASS													
Rated voltage		nominal output voltage ±15 % (settable)											
Rated frequency		50/60 Hz (selectable)											
XMODULE EFF	ICIENCY												
Online double conversion mode		up to 96%											
Fast EcoMode		up to 99%											
ENVIRONMENT	Г												
Operating ambient	temperature	from 10 °C up to +40° °C (from 15 °C to 25 °C for maximum battery life)											
Relative humidity		0 % - 95 % without condensation											
Maximum altitude		1000 m without derating (max. 3000 m)											
STANDARDS													
Safety		IEC/EN 62040-1, AS 62040.1.1, AS 62040.1.2											
EMC		IEC/EN 62040-2, AS 62040.2											
Performance		IEC/EN 62040-3, AS 62040.3											
Product declaration	1	CE, RCM (E2376)											

(1) IGBT rectifier. (2) Conditions apply. (3) With input THDV < 1 %.



DELPHYS Xtend GP

Three-phase UPS

Green Power 2.0 range up to 2.4 MVA/MW

An innovative way to provide scalability



AC CABINET

System input and output.

- General input(s) and output power connection.
- Centralised static bypass, if required.
- \bullet System input(s) and output $\ensuremath{^{(1)}}$ switches.
- Maintenance manual bypass switch(1).

DC CABINET

Prewired coupling for energy storage.

- Energy storage power and control cable connections.
- Connection of up to 6 batteries per system, with dedicated coupling switches.

(1) Please consult us for systems above 1200 kVA/kW (systems in parallel).

Xbay

Easy power block docking.

- Each Xbay dock is prewired to AC and DC cabinets.
- Ready for Xmodule power and control cables connection.
- Includes individual switches for Xmodule AC coupling.
- Hot-plug parallel bus connection.
- The number of Xbay docks depends on the final power required (up to 6 per system).

Xmodule

Hot-scalable 200 kVA/kW power block.

- Power block ensuring load protection and battery management.
- Up to 6 Xmodule power blocks per system.
- Easy positioning.
- Dedicated switches for easy power block servicing.
- Secured installation both for operators and the application.

Real hot-scalable solution

- Quick and safe scalability to meet evolving demands for energy performance.
- Reliable power that can be increased when needed to rapidly meet changing capacity demands.
- Easy adaptation to site evolutions and constraints thanks to movable blocks.
- Prewired system for additional Xmodule connection and coupling within the system.
- Standard tools required to place and connect the power block.
- Online double conversion mode for load protection during system extensions or maintenance.



600 kW, online double conversion mode



600 kW, online double conversion mode




30 minutes later: 800 kW, online double conversion mode



Green Power 2.0 range up to 2.4 MVA/MW

A complete solution


- Simplifies the In / Out switchboard. The system integrates localised coupling capability.
- Fast and cost-effective scalability as there is no need to connect the additional Xmodule power block(s) to any upstream or downstream panel.
- Keeps the critical applications protected in online double conversion mode during power extension.
- Possibility to parallelise systems up to 2400 kVA/kW (12 Xmodules).



Adaptable disposition

The system disposition and physical connection is easily adapted to your plant:

- Many disposition possibilities (Linear, "U"shaped, "L-shaped").
- The number of Xbay docks can be 6 or fewer per system, depending on the rated power of the infrastructure.
- General input/output AC connections available for top or bottom entry.
- Back-up storage DC connection available for top or bottom entry.



Example of configurations (left to right): linear with 6 Xmodule power blocks, linear with 4 Xmodule power blocks, "U-shape" with 6 Xmodule power blocks.

Innovative battery discharge test

DELPHYS Xtend GP allows a periodical complete and safe battery discharge test without using a resistive load for the back-up time or availability check.


Battery Capacity Re-injection allows significant cost savings and reduces the TCO:

- No need to rent or buy load banks.
- Simplified infrastructure, as there are not any dedicated test bus bars.
- No wasted energy because it is re-used to supply other UPS or applications.
- Less time needed to perform the test as it is easy to programme.

The test is performed at a constant rate of power (full power or partial load). Each individual Xmodule power block is tested separately and feeds back the energy stored in the battery. The energy to be fed back upstream through the rectifier will correspond to the difference between the discharged power and the load consumption.

Example of a battery discharge test.

The test is performed on the 4th Xmodule power block at 200 kW constant power.







MODULYS GP

Unique, fully modular and redundant solution

Green Power 2.0 range from 25 to 600 kVA/kW



The solution for

- > Computer rooms
- > Data centres
- > Banks
- > Healthcare facilities
- > Insurance
- > Telecom

Advantages

- > Ensures absolute business continuity
- Aligns capacity to business demand
- Optimises costs over the full life cycle

Certifications and attestations



Green Power 2.0 MODULYS GP is certified by TÜV SÜD with regard to product safety (EN 62040-1)

Green Power 2.0 MODULYS GP efficiency & performance are tested and verified by TÜV SÜD



SERMA TECHNOLOGIES

Green Power 2.0 MODULYS GP power module MTBF is calculated and verified higher than 1,000,000 hours by SERMA TECHNOLOGIES (IEC 62380)



3REEN 117 A - GREEN 157,



With its flexible modularity providing seamless and risk-free power scalability up to 600 kW, the MODULYS GP range is the ideal solution for unscheduled site upgrades or incremental power evolutions. The installed power can be increased up to 600 kW by adding hot-swap plug-in

Designed with no single point of failure, the MODULYS GP offers all the advantages of the Green Power 2.0 technology.

Fully modular system

power modules for incremental steps of 25 kW.

- Plug-in power module.
- Plug-in battery module.
- Plug-in bypass module.
- Top or bottom connection.
- Top-air exhaust module.

'Forever Young' concept

- Exclusive life cycle extension programme.
- Eliminates end-of-life criticality.
- Based on an electronics-free cabinet + a set of plug-in parts.
- Module compatibility guaranteed for 20+ years.
- Allows for the implementation of future module technology.

Totally redundant design

- N+1, N+x redundancy level.
- Designed for no single point of failure.
- No centralised parallel control.
- Totally independent power modules.
- Redundant parallel bus connection (ring configuration).

Enhanced serviceability performance

- Fast & safe maintenance based on hotswap parts (power modules, bypass, electronic boards).
- Battery can be hot-swapped without shutting down the connected equipment.
- Ready for concurrent maintenance.

Advantages

















Standard electrical features

- Dual input mains.
- Internal maintenance bypass.
- Backfeed protection: detection circuit.
- EBS (Expert Battery System) for battery management.
- Battery temperature sensor.

Electrical options

- External battery cabinet.
- High capacity battery charger.
- ACS synchronisation system.
- Internal backfeed isolation device.

Standard communication features

- User-friendly multilingual interface with colour graphic display.
- Commissioning wizard.
- 2 slots for communication options.

Communication options

- Dry-contact, RS232/485 interfaces.
- MODBUS RTU.
- MODBUS TCP.
- BACnet/IP interface.
- NET VISION: professional WEB/SNMP interface for UPS monitoring and shutdown management of several operating systems.

Remote monitoring service

 LINK-UPS, remote monitoring service that connects your UPS to your Critical Power specialist 24/7.

Technical data						
		MODULYS GP				
	UPS SYSTEM					
Power (Sn)	25 to 200 kVA	to 200 kVA 25 to 400 kVA 25 to 600 kVA				
Power (Pn)	25 to 200 kW	25 to 400 kW	25 to 600 kW			
Number of power modules	1 to 8	1 to 16	1 to 24			
Input / output		3/3				
Redundant configuration	N+x					
INPUT						
Voltage	400 V 3ph+N (340 V to 480 V)					
Frequency	50/60 Hz ±10%					
Power factor / THDI	> 0.99 / < 3%					
OUTPUT						
Power factor		1 (according to IEC/EN 620	040-3)			
Voltage		380/400/415 V ±1% 3p	h+N			
Frequency		50/60 Hz ±0.1%				
Voltage distortion	< 19	% (linear load), < 4% (non-linear load ac	cording to IEC 62040-3)			
Short-circuit current	up to 3 x In					
Overload		125% for 10 minutes, 150% fo	or 1 minute			
Crest factor	3:1					
BYPASS						
Voltage	rated output voltage ±15% (configurable with from 10% to 20%)					
Frequency	50/60 Hz ±2% (configurable for GenSet compatibility)					
EFFICIENCY (TÜV SÜD VI	ERIFIED)					
Online double conversion mode		up to 96.5%				
ENVIRONMENT						
Ambient temperature	0 °C to 40 °C (15 to 25 °C for maximum battery life)					
Relative humidity	0 to 95% without condensation					
Maximum altitude	1000 m without derating (3000 m max)					
Acoustic level at 1 m		< 55 dBA				
SYSTEM CABINET						
Width	600 mm	2 x 600 mm (combinable system) 2010 mm (fully integrated solution)	3 x 600 mm (combinable system) 2610 mm (fully integrated solution)			
Depth		890 mm				
Height	1975 mm					
Weight (empty cabinet)	210 kg	2 x 210 kg (combinable system) 780 kg (fully integrated solution)	3 x 210 kg (combinable system) 1010 kg (fully integrated solution)			
Degree of protection		IP20				
STANDARDS						
Safety	IEC/EN 62040-1, AS 62040.1.1, AS 62040.1.2					
EMC	IEC/EN 62040-2 Class C2, AS 62040.2					
Performance	IEC/EN 62040-3, AS 62040.3					
Seismic compliance	On request according to Uniform Building Code UBC-1997 Zone 4					
Environmental	IEC/EN 62040-4					
Product declaration		CE, RCM (E2376)				
POWER MODULE						
Height	3U					
Weight	34 kg					
Туре	Hot plug-in / Hot-swappable					
MTBF	> 1 000 000 hours (calculated and verified)					

Best practice award



Frost & Sullivan has has awarded SOCOMEC with its prize for Innovation & Excellence in Developing Scalable, Best-in-Class Products and Solutions.

SOCOMEC's vast expertise and technological know-how in modular UPS solutions have enabled it to develop a new modular, three-phase UPS that employs the latest cutting-edge technology combined in a unique design and architecture.

The benefit of a fully modular system

Easy to manage

- Totally modular system for power scaling or for quickly adapting to business changes.
- Standardised system and modules covering a wide range of power and back-up times.
- Repeatable and standardised scalable architecture for time-saving design for different configuration & architecture requirements.

Pay as you need

- No prior expenditure for unpredictable future extensions in power and back-up time.
- Space saving thanks to reduced footprint and front access.
- Eliminates installation rework costs when new capacity is required from IT physical infrastructure.
- No risk of design oversizing due to project data uncertainty.

Everything front-access

- Connections, switches, manual bypass, static bypass, power modules and all the electric parts have front-access.
- Total footprint is not increased as rear extra clearance for maintenance is not needed.
- Easy, quick, comfortable, safe and risk-free installation and maintenance.
- More reliable system.

The benefit of a totally redundant design

Total resilience

- Electronics-free (failure-free) cabinet.
- Totally independent and self-sufficient modules.
- Real module selective disconnection with galvanic separation.
- No centralised control for parallel and load sharing management.
- Totally segregated, fully sized and centralised bypass.
- Configurable N+1 to N+x redundancy (power & battery).
- No single point of failure.
- Redundant parallel bus connection (ring configuration).

Optimum reliability

- Power module designed for superior robustness proved by an independent body (MTBF > 1,000,000 hr).
- Highly robust bypass (MTBF > 10,000,000 hr).
- Acid leak-proof modular battery box.


Maximum availability

- Fast recovery of lost redundancy thanks to minimum MTTR (Mean Time To Repair).
- No risk of downtime during power upgrading and maintenance.
- No risk of failure propagation.

Cost-effective redundancy

- No need to duplicate the system hardware to get redundancy.
- Redundancy achievable simply by adding one more power and battery module.
- Redundancy can be easily combined with power scalability.

A flexible modular UPS system




Fully integrated solution

- UPS system cabinets + coupling cabinet + base plates.
- It allows a complete, simple and very reliable installation, with unique IN/OUT and fully sized manual bypass.
- Innovative base plates simplify the installation and allow a tidy and segregated cabling for higher system reliability.

25-400 kW → -25-600 kW →

Combinable system


- It allows the creation of a system when:
 - an external coupling cabinet is already present (i.e. in case of replacement of an existing UPS),
 - a coupling cabinet with a special configuration is required and it has to be developed specifically,
 - the UPS system cabinets cannot be installed side-by-side.




EEN 160 A

Green Power 2.0 range from 25 to 600 kVA/kW


Fully integrated solution: easy and safe installation




Innovative base plates simplify the installation.




Safe, reliable and time-saving cabling management.




Cabinets are easy to move (no pallet truck required), position and assemble.



Easy cabling for a tidy and reliable solution.



Simplified cable positioning and risk-free connections.



Automatic self-configuring hot-swap plug-in power modules.



Three-phase UPS


Green Power 2.0 range from 25 to 600 kVA/kW

Seamless and risk-free scalability & upgrading

- MODULYS GP protects critical loads in all conditions, including power upgrading and maintenance procedures.
- No risk of human error and downtime.


On-line power scalability

• MODULYS GP allows you to increase power scalability and redundancy while keeping the load protected on inverter mode simply by pluggingin a new power module and waiting for its automatic self-configuration, without any human intervention.



Power module automatic firmware alignment

- Even the power module firmware alignment is totally risk free.
- When a new power module is plugged in, the system checks what firmware version is embedded and if it is different automatically aligns it to one of the other modules. The load is protected at all times while running on inverter mode.



On-line global firmware update

- It is also possible to upgrade the global firmware without switching to bypass to keep the load protected on Inverter mode.
- Automatic procedure for a risk-free firmware upgrade.




Flexible and modular back-up times

MODULYS GP offers modular solutions to meet all your requirements for back-up times (whether a few minutes or several hours) without compromising flexibility and scalability.


Internal hot swap battery

- Designed for short back-up time.
- Long-Life batteries available as standard.
- Compact solution with a small footprint.




Modular hot-swap battery cabinets

- Designed for medium and long back-up times.
- Long-Life batteries available as standard.
- Vertical and horizontal modularity ensuring flexible back-up times.



Modular battery cabinet

- Designed for long back-up times.
- Long-Life batteries available as standard.
- Horizontal modularity ensuring flexible back-up times.





MODULYS GP "Forever Young" concept

- MODULYS GP excels not only in efficiency, flexibility, capacity management and sustainability - five aspects that are crucial for optimum performance.
- It employs an exclusive concept called 'Forever Young' which allows the life-cycle extension of MODULYS GP and eliminates the criticality of system end-of-life.
- It also keeps the system open for the implementation of future technology improvements without modifying the infrastructure.

The 'Forever Young' concept:

- Is based on electronics-free (failure-free) cabinets where the components that are subject to ageing are all plug-in and therefore quick and easy to replace.
- Allows life-cycle extension via periodic replacement of power modules before they start ageing.
- Provides an always up-to-date system that uses the latest technology.
- Assures power modules and spare part compatibility and availability for more than 20 years.









MODULYS RM GP

Rack-mounted modular UPS system

Green Power 2.0 range up to 4 x 25 kW



Full rack integration

- Designed for easy and no-risk integration in 19" rack cabinets.
- Total compatibility with any 19" standard rack cabinet.
- · High power density.
- Easy to manage, integrate and customise.
- Flexible simplified cabling.

Overall cost optimisation

- Time saving integration process.
- No risk of cost and budget overruns.
- Compact solution saving valuable space.
- Simplified logistics.
- Easy integration: avoids costly set-up and reworking.

Totally redundant design

- N+1 redundancy level.
- Designed for no single point of failure.
- No centralised parallel control.
- Totally independent power modules.

Enhanced serviceability performance

- Fast & safe maintenance based on hotswap parts (power modules, bypass, electronic boards, batteries).
- Ready for concurrent maintenance.
- Battery can be hot-swapped without shutting down the connected equipment.

'Forever Young' concept

- Exclusive life cycle extension programme.
- Eliminates end-of-life criticality.
- Based on an electronics-free sub-rack enclosure + a set of plug-in parts.
- Module compatibility guaranteed for 20+ vears.
- Allows for the implementation of future module technology.

The solution for

- Integration in 19" standard rack cabinets
- > Computer rooms
- > Data centers
- > Banks
- > Healthcare facilities
- > Insurance
- > Telecom

Certifications and attestations



Green Power 2.0 MODULYS RM GP module is certified by TÜV SÜD with regard to product safety (EN 62040-1).

Green Power 2.0 MODULYS module efficiency & performance are tested and verified by TÜV SÜD.



SERMA TECHNOLOGIES

Green Power 2.0 MODULYS RM GP module MTBF is calculated and verified 1,000,000 hours by SERMA TECHNOLOGIES (IEC 62380).



Advantages







Highest rack-mounted UPS power density





Unity power factor provides the best €/kW ratio



High efficiency minimises energy consumption and reduces energy costs



Ready for Li-lon battery. Ultra-fast recharge function





Three-phase UPS

Standard electrical features

- Dual input mains.
- Internal maintenance bypass.
- Backfeed protection: detection circuit.
- EBS (Expert Battery System) for battery management.
- Battery temperature sensor.

Electrical options

- 19" 4U battery rack.
- External battery cabinet.
- High capacity battery charger.
- ACS synchronization system.

Standard communication features

- User-friendly multilingual interface with color graphic display.
- 2 slots for communication options.

Communication options

- Dry-contact, RS232/485 interfaces.
- MODBUS RTU.
- MODBUS TCP.
- BACnet/IP interface.
- NET VISION: professional WEB/SNMP interface for UPS monitoring and shutdown management of several operating systems.

Total resilience

- Electronics-free (failure-free) sub-rack enclosure.
- Totally independent and self-sufficient modules.
- Real selective module disconnection with galvanic separation.
- No centralised control for parallel and load sharing management.
- Totally segregated, fully sized and centralised auxiliary mains bypass and distributed inverter bypass.
- Configurable N+1 redundancy (power & battery).
- No single point of failure.
- Redundant parallel bus connection (ring configuration).

Technical data

	MODULYS RM GP				
Model	9U 15U				
Number of power modules	1 to 2 x 25 kW 1 to 4 ⁽¹⁾ x 25 kW				
Configuration	N, N+1 redundant				
Power (Sn)	25 to 50 kVA	25 to 75 kVA			
Power (Pn)	25 to 50 kW	25 to 75 kW			
Input/output	3/3	3			
INPUT					
Voltage	400 V 3ph (340 V to 480 V)				
Frequency	50/60 Hz ±10%				
Power factor/THDI	> 0.99/< 3%				
OUTPUT					
Voltage	380/400/415 V	′ ±1 % 3ph+N			
Frequency	50/60 Hz	±0.1%			
Voltage distortion	< 1 % (linear load), < 4 % (non-linear	ar load according to IEC 62040-3)			
Short-circuit current	up to 3 x ln				
Overload	125 % for 10 minutes, 150 % for 1 minute				
Crest factor	3:1				
HOT-SWAP BYPASS					
Voltage	Rated output voltage ±15% (configurable from 10% to 20%)				
Frequency	50/60 Hz ±2% (configurable	e for GenSet compatibility)			
Weight	7 kg	7.5 kg			
EFFICIENCY (TÜV SÜD VERIFIED)					
Online double conversion mode	up to 90	6.5 %			
ENVIRONMENT					
Ambient temperature	0 °C to 40 °C (15 to 25 °C for maximum battery life)				
Relative humidity	0 to 95 % without condensation				
Maximum altitude	1000 m without derating (3000 m max)				
Acoustic level at 1 m	< 53 (dBA			
UPS RACK					
Dimensions W x D x H	442 mm x 920 mm x 9 U	442 mm x 920 mm x 15 U			
Weight (empty cabinet)	36 kg 42 kg				
Degree of protection	IP2	0			
HOT-SWAP POWER MODULE					
Height	3U				
Weight	34 kg				
Туре	Hot plug-in/Ho	t-swappable			
MTBF	> 1000000 hours (cal	culated and verified)			
HOT-SWAP BATTERY RACK					
Туре	Acid leak-proof - Long Life batteries				
Protection	Independent protection for each battery string				
Dimensions W x D x H	442 mm x 890 mm x 4 U				
Weight (empty rack)	15 k	kg			
STANDARDS					
Safety	EN 62040-1, I	EN 60950-1			
EMC	EN 62040-2 Class C2				
Performance	EN 62040-3 (VFI-SS-111)				
Product certification	CE				

16011110ai uata

Product certification (1) 4th module is for redundancy.

Optimum reliability

- Power module designed for superior robustness verified by an independent body (MTBF > 1,000,000 hr).
- Highly robust bypass (MTBF > 10,000,000 hr)
- Acid leak-proof modular battery box.

Maximum availability

- Fast recovery of lost redundancy thanks to minimum MTTR (Mean Time To Repair).
- No risk of downtime during power upgrading and maintenance.
- No risk of failure propagation.

The benefit of a system designed for 19" rack integration

Easy to integrate

- Specifically designed for integration in 19" standard rack cabinets.
- · Adjustable rails and mounting accessories.
- High power density (>6 kW/U).
- · Low weight for easy integration.
- Pre-cabled system for simplified connections.
- Flexible cabling management for top, bottom and mixed top/bottom entry cable.
- Integrated cables organiser for tidy connections.
- Low power dissipation (<40 W per supplied kW).

No-risk integration

- Assured compatibility with any 19" standard rack cabinet.
- Pre-engineered and lab-tested parts assuring total system reliability.
- Automatic self-configuration power modules.
- No risk of design oversize due to project data uncertainty thanks to power module scalability.

Easy to customise

- Complete set of pre-engineered and pre-tested parts to meet any customer need:
 - modular Power Modules,
 - special power modules with extra battery charger for extremely long BUT,
 - plug-in J-BUS communication board for BMS integration,
 - plug-in SNMP board for UPS monitoring and shutdown management,
 - plug-in programmable dry-contact board,
- environmental sensors,
- blank panels (covers for empty slots),
- rack-mounted battery modules,
- external battery cabinet,
- isolation transformer,
- bypass redundant cooling.

Easy to manage

- Full documentation package including schematics, integration instructions, technical sheets, etc.
- Factory-set configurations for easy model selection.
- Full set of pre-engineered options for easy product customisation.

Pre-cabled system for simplified connections





Example of integration (3x25 kW).
Only 15 U of rack space occupied: space-saving design leaving free space for other rack-mounted devices. One empty slot in the MODULYS RM GP sub-rack remains available for power upgrade or redundancy.



Rear view (before adding rear protective cover). Flexible cabling management for easy connections and tidier cabling.



Green Power 2.0 range up to 4 x 25 kW

Overall cost optimisation

- Compact sub-rack enclosure saving valuable cabinet rack space.
- 2 sub-rack enclosure models for optimum sizing.
- Best-in-class €/kW ratio thanks to high power density and PF=1.
- Cost-optimised solution for minimum initial investment.
- Plug & Play and self-configuration power modules for easy and time saving system set up.
- Pre-engineered and lab-tested parts for easy and time saving customisation.
- Repeatable and standardised architecture for time saving design and know-how capitalisation.


Simplified logistics

- Fewer standardised parts for easy ordering.
- Parts always in stock for fast procurement.
- Fewer parts covering a wide range of configurations, power, back-up time and options.
- Once integrated in the 19" rack cabinet, MODULYS RM GP can be safely shipped with the power modules plugged in.

Compact 15U sub-rack enclosure

Designed for complete integration in any 19" standard rack cabinet.





M4-RI-OP-RAIL Adjustable rails for rack mounting support



Socomec worldwide

IN EUROPE

BELGIUM

Critical Power / Power Control & Safety / Energy Efficiency

Tel. +32 2 340 02 30 Fax +32 2 346 28 99 info.be@socomec.com

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +33 1 45 14 63 00 Fax +33 1 48 67 31 12 dcm.ups.fr@socomec.com

GERMANY

Critical Power

Tel. +49 621 71 68 40 Fax +49 621 71 68 444 info.ups.de@socomec.com

Power Control & Safety / Energy Efficiency

Tel. +49 7243 65292 0 Fax +49 7243 65292 13 info.scp.de@socomec.com

Critical Power

Tel.+39 02 98 242 942 Fax +39 02 98 240 723 info.ups.it@socomec.com

Power Control & Safety / Energy Efficiency

Tel.+39 02 98 49 821 Fax +39 02 98 24 33 10 info.scp.it@socomec.com

NETHERLANDS

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +31 30 760 0900 Fax +31 30 637 2166 info.nl@socomec.com

POLAND

Critical Power

Tel. +48 22 825 73 60 Fax. +48 22 825 73 70 info.ups.pl@socomec.com

Power Control & Safety / Energy Efficiency

Tel. +48 91 442 64 11 Fax +48 91 442 64 19 info.scp.pl@socomec.com

PORTUGAL

Critical Power / Power Control & Safety / Energy Efficiency

Tel.+351 261 812 599 Fax +351 261 812 570 info.ups.pt@socomec.com

ROMANIA

Critical Power / Power Control & Safety / Energy Efficiency

Tel. +40 21 319 36 88 Fax +40 21 319 36 89 info.ro@socomec.com

SERBIA

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +381 11 40 43 246 Fax +381 11 40 43 245 info.rs@socomec.com

SLOVENIA

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +386 1 5807 860 Fax +386 1 561 11 73 info.si@socomec.com

SPAIN

Critical Power / Power Control & Safety / Energy Efficiency

Tel. +34 93 540 75 75 Fax +34 93 540 75 76 info.es@socomec.com

SWITZERLAND

Critical Power

Tel. +41 44 745 40 80 Fax +41 44 745 40 85 info@socomec.ch

TURKEY

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +90 216 540 71 20-21-22 Fax +90 216 540 71 27 info.tr@socomec.com

UNITED KINGDOM

Critical Power

Tel. +44 1285 863 300 Fax +44 1285 862 304 info.uk@socomec.com

Power Control & Safety / Energy Efficiency

Tel. +44 1462 440 033 Fax +44 1462 431 143 info.uk@socomec.com

IN ASIA PACIFIC

AUSTRALIA

Critical Power / Power Control & Safety

Tel. +61 2 9325 3900 Fax +61 2 9888 9544 info.ups.au@socomec.com

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +86 21 52 98 95 55 Fax +86 21 62 28 34 68 info.cn@socomec.com

INDIA

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +91 44 39215400 Fax +91 44 39215450 & 51 info.in@socomec.com

SINGAPORE

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel.+65 6506 7600 Fax +65 64 58 7377 info.sg@socomec.com

THAILAND

Critical Power

Tel. +66 2 941 1644 7 Fax +66 2 941 1650 info.ups.th@socomec.com

IN MIDDLE EAST

UNITED ARAB EMIRATES

Critical Power / Power Control & Safety / **Energy Efficiency**

Tel. +971 4 29 98 441 Fax +971 4 29 98 449 info.ae@socomec.com

IN AMERICA

USA, CANADA & MEXICO

Power Control & Safety / Energy Efficiency

Tel. +1 617 245 0447 Fax +1 617 245 0437 info.us@socomec.com

OTHER COUNTRIES

NORTH AFRICA

Algeria / Morocco / Tunisia info.naf@socomec.com

Other countries

info.africa@socomec.com

SOUTH EUROPE

Cyprus / Greece / Israel / Malta info.se@socomec.com

SOUTH AMERICA

Tel. +34 93 540 75 75 info.es@socomec.com

MORE DETAILS

www.socomec.com/worldwide

HEAD OFFICE

SOCOMEC GROUP

SAS SOCOMEC capital 10 686 000 € R.C.S. Strasbourg B 548 500 149 B.P. 60010 - 1, rue de Westhouse F-67235 Benfeld Cedex - FRANCE Tel. +33 3 88 57 41 41 Fax +33 3 88 74 08 00 info.scp.isd@socomec.com

YOUR DISTRIBUTOR / PARTNER



www.socomec.com











